



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .281 (7.137mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .020 (.508mm)	F IN (mm) +/- .030 (.762mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING
	MIN IN (mm)	MAX IN (mm)									
AP(R, L)-08-120-9	.187 (4.75mm)	2.06 (52.3mm)	8.700 (220.980mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	V-2	AH-2
AP(R, L)-08-120-0	.187 (4.75mm)	2.06 (52.3mm)	8.700 (220.980mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	V-2	AH-2
AP(R, L)-14-120-9	.187 (4.75mm)	4.0625 (103.187mm)	14.828 (376.631mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	V-2	AH-2
AP(R, L)-14-120-0	.187 (4.75mm)	4.0625 (103.187mm)	14.828 (376.631mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	V-2	AH-2
AP(R, L)-18-120-9	.187 (4.75mm)	5.000 (127.000mm)	18.250 (463.550mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2
AP(R, L)-18-120-0	.187 (4.75mm)	5.000 (127.000mm)	18.250 (463.550mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2
AP(R, L)-24-120-9	.187 (4.75mm)	7.000 (177.800mm)	24.500 (622.300mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2
AP(R, L)-24-120-0	.187 (4.75mm)	7.000 (177.800mm)	24.500 (622.300mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2
AP(R, L)-30-120-9	.187 (4.75mm)	9.000 (228.600mm)	30.875 (784.225mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2
AP(R, L)-30-120-0	.187 (4.75mm)	9.000 (228.600mm)	30.875 (784.225mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2
AP(R, L)-36-120-9	.187 (4.75mm)	11.000 (279.400mm)	37.125 (942.975mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2
AP(R, L)-36-120-0	.187 (4.75mm)	11.000 (279.400mm)	37.125 (942.975mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2



120 LB. LIGHT HEAVY DUTY SERIES CABLE TIES

D	10/8/18	EG	DW	EG	REVISED 14" TIE DIMENSIONS	COLOR DESIGNATIONS: 0 = UV BLACK 9 = NATURAL	MATERIAL: NYLON 6/6 POLYAMIDE		
C	3/8/18	PB	EG	EG	UPDATED PART DESCRIPTION MATCH CATALOG		SHEET 1 OF 1	REV.: D DRAWING NO.: 120-D	
B	5/1/17	JA	KT	KT	NEW LOGO ADDED	DRAWN BY	DATE	CHECK	SCALE
A	12/22/14	JA	KT	KT	INITIAL RELEASE	JA	5/1/17	KT	NONE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION				

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.48.2