



4" Head Configuration



6" & 8" Head Configuration

ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER	A IN (mm) +/- .030 (.889mm)	B IN (mm) +/- .010 (.250mm)	C IN (mm) +/- .030 (.889mm)	D IN (mm) +/- .010 (.250mm)	E IN (mm) +/- .014 (.360mm)	ANSI/UL 94 MII FLAMABILITY RATING
	MAX IN (mm)						
AP(R, L)-04-BD-9	.985 (25.019mm)	4.075 (103.50mm)	.050 (1.270mm)	3.250 (82.55mm)	.101 (2.565mm)	.197 (5.003mm)	V-2
AP(R, L)-06-BD-9	1.418 (36.017mm)	5.750 (146.05mm)	.062 (1.574mm)	5.135 (130.429mm)	.110 (2.794mm)	.310 (7.874mm)	V-2
AP(R, L)-08-BD-9	2.045 (51.943mm)	7.875 (200.025mm)	.066 (1.676mm)	7.718 (196.056mm)	.110 (2.794mm)	.310 (7.874mm)	V-2



BEADED CABLE TIES

D	6/26/19	DW	RB	RB	REMOVE TENSILE STRENGTH	COLOR DESIGNATIONS: 9 = NATURAL	MATERIAL: NYLON 6/6 POLYAMIDE		
C	3/20/18	PB	EG	EG	UPDATED TO VENDOR SPECS				
B	4/27/17	JA	KT	KT	NEW LOGO ADDED.	SHEET 1 OF 1	REV.: D	DRAWING NO.: BD-D	
A	4/28/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	4/27/17	RB	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.69.3