



ADVANCED CABLE TIES PART NUMBER					A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	G IN (mm) +/- .005 (.127mm)	TAB SIZE	STOCK THICKNESS	TAB	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-CFR4NA250F-N-C					.89 (22.6mm)	.38 (9.7mm)	.16 (4.1mm)	.20 (5.1mm)	.250" X .032"	.016 (.41)	.250 X .032	RED/NYLON	22-18	UL
AL-CFR4NB250F-N-C					.89 (22.6mm)	.38 (9.7mm)	.16 (4.1mm)	.20 (5.1mm)	.250" X .032"	.016 (.41)	.250 X .032	BLUE/NYLON	16-14	UL
					 <b>ACT</b> ADVANCED CABLE TIES, INC.									
					DOUBLE CRIMP NYLON FULLY INSULATED FEMALE DISCONNECTS									
					<b>COLOR:</b> RED, BLUE & YELLOW					<b>MATERIAL:</b> NYLON 6/6				
B	10/21/21	DW	RB	RB	ISO DOC				SHEET 1 OF 1	<b>REV.: B</b>		DRAWING NO.: DC-NY-FM-DIS-B		
A	6/26/14	JA	KT	KT	INITIAL RELEASE				DRAWN BY	DATE	CHECK	SCALE		
<b>REV</b>	<b>DATE</b>	<b>BY</b>	<b>CHK</b>	<b>APPROVE</b>	<b>DESCRIPTION</b>				JA	6/26/14	KT	NONE		

**CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.**  
**THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.**