


ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	TAB SIZE	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-FR4A250-N-C	.31 (7.9mm)	.43 (10.9mm)	.115 (2.92mm)	.865 (21.97mm)	.156 (3.96mm)	.301 (7.65mm)	.250" X .032"	RED/NYLON	22-18	UL
AL-FR4B250-N-C	.31 (7.9mm)	.43 (10.9mm)	.138 (3.51mm)	.865 (21.97mm)	.156 (3.96mm)	.301 (7.65mm)	.250" X .032"	BLUE/NYLON	16-14	UL
AL-FR4C250-N-C	.31 (7.9mm)	.57 (14.5mm)	.225 (5.70mm)	1.011 (25.68mm)	.156 (3.96mm)	.301 (7.65mm)	.250" X .032"	YELLOW/NYLON	12-10	UL
										
							COLOR:		MATERIAL:	
							RED, BLUE & YELLOW		NYLON 6/6	
B	10/21/21	DW	RB	RB	ISO DOC		SHEET 1 OF 1	REV.: B	DRAWING NO.: DC-NY-FM-DIS-B	
A	6/26/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	6/26/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.111.2

