



ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	G IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-FR4A250-N-C	.842 (21.387mm)	.115 (2.921mm)	.061 (1.549mm)	.420 (10.668mm)	.360 (9.144mm)	.160 (4.064mm)	.290 (7.366mm)	RED/NYLON	22-18	UL/CSA
AL-FR4B250-N-C	.850 (21.590mm)	.140 (3.556mm)	.082 (2.083mm)	.420 (10.668mm)	.360 (9.144mm)	.160 (4.064mm)	.290 (7.366mm)	BLUE/NYLON	16-14	UL/CSA
AL-FR4C250-N-C	.986 (25.044mm)	.235 (5.969mm)	.148 (3.759mm)	.550 (13.970mm)	.344 (8.738mm)	.160 (4.064mm)	.290 (7.366mm)	YELLOW/NYLON	12-10	UL/CSA
										
					<b>ADVANCED CABLE TIES – DOUBLE CRIMP NYLON INSULATED FEMALE DISCONNECTS</b>					
					<b>COLOR: RED, BLUE &amp; YELLOW</b>			<b>MATERIAL: NYLON 6/6</b>		
					<b>SHEET 1 OF 1</b>		<b>REV.: A</b>		<b>DRAWING NO.: DC-NY-FM-DIS-A</b>	
A	6/26/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY		DATE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA		6/26/14	
<b>CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.</b> <b>THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.</b>										