


ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	G IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-S4A-6-N-C	1.029 (26.137mm)	.064 (1.625mm)	.163 (4.140mm)	.535 (13.589mm)	.302 (7.671mm)	.148 (3.759mm)	.320 (8.128mm)	RED/NYLON	22-18	UL/CSA
AL-S4A-10-N-C	1.012 (25.705mm)	.064 (1.625mm)	.158 (4.013mm)	.526 (13.360mm)	.285 (7.239mm)	.200 (5.080mm)	.320 (8.128mm)	RED/NYLON	22-18	UL/CSA
AL-S4B-6-N-C	1.028 (26.111mm)	.089 (2.260mm)	.190 (4.826mm)	.535 (13.589mm)	.271 (6.883mm)	.148 (3.759mm)	.364 (9.246mm)	BLUE/NYLON	16-14	UL/CSA
AL-S4B-10-N-C	1.031 (26.187mm)	.089 (2.260mm)	.193 (4.902mm)	.535 (13.589mm)	.261 (6.629mm)	.200 (5.080mm)	.393 (9.982mm)	BLUE/NYLON	16-14	UL/CSA
AL-S4C-6-N-C	1.187 (30.150mm)	.132 (3.353mm)	.254 (6.452mm)	.657 (16.688mm)	.322 (8.179mm)	.144 (3.658mm)	.377 (9.576mm)	YELLOW/NYLON	12-10	UL/CSA
AL-S4C-10-N-C	1.188 (30.150mm)	.132 (3.353mm)	.254 (6.452mm)	.657 (16.688mm)	.303 (7.696mm)	.194 (4.928mm)	.374 (9.500mm)	YELLOW/NYLON	12-10	UL/CSA
								ADVANCED CABLE TIES – DOUBLE CRIMP NYLON INSULATED SPADE TERMINALS		
COLOR: RED, BLUE & YELLOW								MATERIAL: VINYL		
					SHEET 1 OF 1	REV.: A		DRAWING NO.: DC-NY-SP-TERM-A		
A	6/6/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	6/6/14	KT	NONE
CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC. THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.										