


ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	TAB	COLOR	COPPER COND. RANGE	REGULATORY		
AL-CFR4NA250F-HS-Q	1.50 (38.1mm)	.17 (4.3mm)	.081 (2.05mm)	.39 (9.9mm)	.250 X .032	RED	22-18	UL		
AL-CFR4NB250F-HS-Q	1.50 (38.1mm)	.18 (4.5mm)	.081 (2.05mm)	.39 (9.9mm)	.250 X .032	BLUE	16-14	UL		
AL-CFR4NC250F-HS-Q	1.52 (38.6mm)	.23 (5.8mm)	.140 (3.56mm)	.39 (9.9mm)	.250 X .032	YELLOW	12-10	UL		
										
					HEAT SHRINK FULLY INSULATED FEMALE DISCONNECTS					
					<b>COLOR:</b> RED, BLUE & YELLOW		<b>MATERIAL:</b> HEAT SHRINK			
B	10/21/21	DW	RB	RB	ISO DOC		SHEET 1 OF 1	REV.: B	DRAWING NO.: HS-FI-FM-DC-B	
A	6/27/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	6/27/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.119.2