



ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	COLOR	COPPER COND. RANGE	REGULATORY
AL-R4A-10-HS-Q	1.363 (34.620mm)	.028 (.711mm)	.235 (5.969mm)	.065 (1.651mm)	.200 (5.080mm)	.313 (7.950mm)	RED	22-18	UL/CSA
AL-R4B-10-HS-Q	1.323 (33.604mm)	.035 (.889mm)	.235 (5.969mm)	.088 (2.235mm)	.200 (5.080mm)	.313 (7.950mm)	BLUE	16-14	UL/CSA
AL-R4B-14-HS-Q	1.463 (37.160mm)	.032 (.813mm)	.235 (5.969mm)	.088 (2.235mm)	.266 (6.756mm)	.465 (11.811mm)	BLUE	16-14	UL/CSA
AL-R4B-56-HS-Q	1.489 (37.821mm)	.032 (.813mm)	.235 (5.969mm)	.088 (2.235mm)	.328 (8.331mm)	.465 (11.811mm)	BLUE	16-14	UL/CSA
AL-R4B-38-HS-Q	1.660 (42.164mm)	.040 (1.016mm)	.235 (5.969mm)	.088 (2.235mm)	.386 (9.799mm)	.536 (13.614mm)	BLUE	16-14	UL/CSA
AL-R4C-10-HS-Q	1.369 (34.773mm)	.040 (1.016mm)	.315 (8.001mm)	.130 (3.302mm)	.194 (4.928mm)	.375 (9.525mm)	YELLOW	12-10	UL/CSA
AL-R4C-14-HS-Q	1.484 (37.694mm)	.040 (1.016mm)	.300 (7.620mm)	.130 (3.302mm)	.264 (6.706mm)	.530 (13.462mm)	YELLOW	12-10	UL/CSA
AL-R4C-38-HS-Q	1.638 (41.605mm)	.043 (1.092mm)	.300 (7.620mm)	.130 (3.302mm)	.385 (9.779mm)	.590 (14.986mm)	YELLOW	12-10	UL/CSA



ADVANCED CABLE TIES – HEAT SHRINK RING TERMINALS

COLOR: RED, BLUE & YELLOW

MATERIAL:

HEAT SHRINKABLE TUBING

SHEET 1 OF 1

REV.: A

DRAWING NO.: HS-RT-A

REV	DATE	BY	CHK	APPROVE	DESCRIPTION	DRAWN BY	DATE	CHECK	SCALE
A	6/26/14	JA	KT	KT	INITIAL RELEASE	JA	6/26/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.