



ADVANCED CABLE TIES PART NUMBER	STUD SIZE	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D-MIN. IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .010 (.25mm)	F IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-S4A-6-HS-Q	6	1.40 (35.6mm)	.028 (.71mm)	.235 (5.97mm)	.054 (1.37mm)	.146 (3.71mm)	.323 (8.20mm)	RED	22-18	UL
AL-S4A-8-HS-Q	8	1.40 (35.6mm)	.028 (.71mm)	.235 (5.97mm)	.054 (1.37mm)	.173 (4.39mm)	.323 (8.20mm)	RED	22-18	UL
AL-S4A-10-HS-Q	10	1.40 (35.6mm)	.028 (.71mm)	.235 (5.97mm)	.054 (1.37mm)	.198 (5.03mm)	.323 (8.20mm)	RED	22-18	UL
AL-S4B-6-HS-Q	6	1.42 (36.1mm)	.031 (.79mm)	.235 (5.97mm)	.084 (2.13mm)	.146 (3.71mm)	.37 (9.4mm)	BLUE	16-14	UL
AL-S4B-8-HS-Q	8	1.42 (36.1mm)	.031 (.79mm)	.235 (5.97mm)	.084 (2.13mm)	.173 (4.39mm)	.40 (10.2mm)	BLUE	16-14	UL
AL-S4B-10-HS-Q	10	1.42 (36.1mm)	.031 (.79mm)	.235 (5.97mm)	.084 (2.13mm)	.198 (5.03mm)	.40 (10.2mm)	BLUE	16-14	UL
AL-S4C-8-HS-Q	8	1.39 (35.3mm)	.040 (1.02mm)	.310 (7.62mm)	.128 (3.25mm)	.173 (4.39mm)	.39 (9.9mm)	YELLOW	12-10	UL



HEAT SHRINK SPADE TERMINALS

COLOR: RED, BLUE & YELLOW MATERIAL: HEAT SHRINK

B	10/21/21	DW	RB	RB	ISO DOC	SHEET 1 OF 1	REV.: B	DRAWING NO.: HS-SP-TERM-B		
A	1/22/15	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	1/22/15	KT	NONE	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
 THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.