



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER				A	B	C	D	E	F	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING		
	MAX IN (mm)				IN (mm) +/- .039 (1.000mm)	IN (mm) +/- .039 (1.000mm)	IN (mm) +/- .010 (.250mm)	IN (mm) +/- .020 (.520mm)	IN (mm) +/- .014 (.307mm)	IN (mm) +/- .010 (.250mm)				
AP(R, L)-04-18-FL-9	.890 (22.606mm)				4.375 (111.125mm)	3.071 (78.003mm)	.105 (2.667mm)	.797 (20.243mm)	.361 (9.169mm)	.041 (1.041mm)	18 (80)	V-2		
18 LB. FLAG SERIES CABLE TIES														
						COLOR DESIGNATIONS: 9 = NATURAL			MATERIAL: NYLON 6/6 POLYAMIDE					
C	3/12/18	PB	EG	EG	UPDATING TO VENDOR SPECS						SHEET 1 OF 1	REV.: C	DRAWING NO.: 4-FL-C	
B	4/27/17	JA	KT	KT	NEW LOGO ADDED.						DRAWN BY	DATE	CHECK	SCALE
A	4/29/14	JA	KT	KT	INITIAL RELEASE						JA	4/27/17	KT	NONE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION									

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.