


ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	
AP(R, L)-MPA-750-9	.740 (18.790mm)	.740 (18.790mm)	.152 (3.860mm)	.190 (4.820mm)	.200 (5.080mm)	.050 (1.270mm)	
AP(R, L)-MPA-750-0	.740 (18.790mm)	.740 (18.790mm)	.152 (3.860mm)	.190 (4.820mm)	.200 (5.080mm)	.050 (1.270mm)	
AP(R, L)-MPA-750-MD-22	.740 (18.790mm)	.740 (18.790mm)	.152 (3.860mm)	.190 (4.820mm)	.200 (5.080mm)	.050 (1.270mm)	
AP(R, L)-MPA-1000-9	.990 (25.140mm)	.990 (25.140mm)	.214 (5.436mm)	.200 (5.080mm)	.200 (5.080mm)	.060 (1.520mm)	
AP(R, L)-MPA-1000-0	.990 (25.140mm)	.990 (25.140mm)	.214 (5.436mm)	.200 (5.080mm)	.200 (5.080mm)	.060 (1.520mm)	
AP(R, L)-MPA-1000-MD-22	.990 (25.140mm)	.990 (25.140mm)	.214 (5.436mm)	.200 (5.080mm)	.200 (5.080mm)	.060 (1.520mm)	
							
F	9/7/21	DW	DW	RB	UPDATED ADHESIVE SPECIFICATIONS		
E	5/7/20	DW	DW	RB	REMOVED GEL ADHESIVE		
D	12/14/17	PB	VA	VA	CHANGING MOUNTING PADS TO MOUNTING BASES		
C	4/29/17	JA	KT	K	NEW LOGO ADDED		
B	1/22/16	JA	KT	KT	ADDED TAPE AND ADHESIVE SPECIFICATIONS		
A	12/22/14	JA	KT	KT	INITIAL RELEASE		
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		
<b>ACT</b> ADVANCED CABLE TIES, INC.						<b>ADVANCED CABLE TIES – MOUNTING BASE</b> <b>(ACRYLIC BASED ADHESIVE TAPE)</b>	
						<b>COLOR DESIGNATIONS:</b> 0 = BLACK 9 = NATURAL MD-22= METAL DETECTABLE	<b>MATERIAL:</b> <b>NYLON 6/6 POLYAMIDE</b>
						SHEET 1 OF 1	<b>REV.: F</b>
						DRAWING NO.: MOUNTING-BASE-A-F	
						DRAWN BY JA	DATE 4/29/17
						CHECK KT	SCALE NONE
<b>CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.</b>							
<b>THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.</b>							

## ***ADHESIVE SPECIFICATIONS***

### **Shelf Life:**

Two years (stored at 75°F/21°C, 50% relative humidity, out of direct sunlight and in a closed package).

### **Application Temperature Range:**

65°F to 120°F (18°C to 49°C)

### **General Service Temperature Range:**

-4°F to 158°F (-20°C to 70°C)

### **Surface Preparation:**

It is essential that the surface to which the tape is to be applied is clean, dry and free of grease and oil.

### **Surfaces:**

Stainless Steel

ABS

PVC

Nylon

Aluminum

Enamel Painted Steel

Galvanized Steel (Rubber Base Adhesive only)

### **Dwell Time:**

Rubber Base adhesive, 15 minutes to bond, 1 hour for maximum adhesion.

Acrylic Base adhesive, 48 hours to bond, 72 hours for maximum adhesion.

### **UL Recognition, Rubber base and Acrylic tape only:**

The mount and tape together are UL Recognized for indoor use at a maximum temperature rating of 158°F (70°C)