



ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)
AP(R, L)-MP-750-9	.740 (18.790mm)	.740 (18.790mm)	.152 (3.860mm)	.190 (4.820mm)	.200 (5.080mm)	.050 (1.270mm)
AP(R, L)-MP-750-0	.740 (18.790mm)	.740 (18.790mm)	.152 (3.860mm)	.190 (4.820mm)	.200 (5.080mm)	.050 (1.270mm)
AP(R, L)-MP-750-MD-22	.740 (18.790mm)	.740 (18.790mm)	.152 (3.860mm)	.190 (4.820mm)	.200 (5.080mm)	.050 (1.270mm)
AP(R, L)-MP-1000-9	.990 (25.140mm)	.990 (25.140mm)	.214 (5.436mm)	.200 (5.080mm)	.200 (5.080mm)	.060 (1.520mm)
AP(R, L)-MP-1000-0	.990 (25.140mm)	.990 (25.140mm)	.214 (5.436mm)	.200 (5.080mm)	.200 (5.080mm)	.060 (1.520mm)
AP(R, L)-MP-1000-MD-22	.990 (25.140mm)	.990 (25.140mm)	.214 (5.436mm)	.200 (5.080mm)	.200 (5.080mm)	.060 (1.520mm)
MOUNTING BASES (RUBBER BASED ADHESIVE TAPE)						
E	5/7/20	DW	DW	RB	REMOVED GEL ADHESIVE SPECIFICATIONS	
D	12/14/17	PB	PB	PB	CHANGING MOUNTING PADS TO MOUNTING BASES	COLOR DESIGNATIONS: 0 = BLACK 9 = NATURAL MD-22= METAL DETECTABLE
C	4/29/17	JA	KT	KT	NEW LOGO ADDED.	
B	1/22/16	JA	KT	KT	ADD TAPE AND ADHESIVE SPECIFICATIONS	MATERIAL: NYLON 6/6 POLYAMIDE
A	12/22/14	JA	KT	KT	INITIAL RELEASE	SHEET 1 OF 1 REV.: E DRAWING NO.: MOUNTING-BASE-R-E
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	DRAWN BY JA DATE 4/29/2017 CHECK KT SCALE NONE

**CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.**

SPC-4.10.64.5

ADHESIVE SPECIFICATIONS

Shelf Life:

Two years (stored at 70°F/21°C, 50% relative humidity, out of direct sunlight and in a closed package).

Application Temperature Range:

65°F to 120°F (18°C to 49°C), Rubber base and Acrylic.

General Service Temperature Range:

-20°F to 180°F (-29°C to 82°C), Acrylic.

0°F to 150°F (-18°C to 65°C), Rubber base.

Surface Preparation:

It is essential that the surface to which the tape is to be applied is clean, dry and free of grease and oil.

Surfaces:

Stainless Steel

ABS

PVC

Nylon

Aluminum

Galvanized Steel (Acrylic Base Adhesive only)

Enamel Painted Steel (Rubber Base Adhesive only)

Dwell Time:

Rubber Base adhesive, 15 minutes to bond, 1 hour for maximum adhesion.

Acrylic Base adhesive, 48 hours to bond, 72 hours for maximum adhesion.

UL Recognition, Rubber base and Acrylic tape only:

The mount and tape together are UL Recognized for indoor use at a maximum temperature rating of 158°F (70°C)