



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .28 (7.13mm)	B IN (mm) +/- .005 (.12mm)	C IN (mm) +/- .010 (.25mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING	
	MIN IN (mm)	MAX IN (mm)							
ALB-04-18-SP-(9,0)	.08 (2.0mm)	.94 (24.0mm)	3.93 (100.0mm)	.035 (.9mm)	.098 (2.5mm)	18 (80)	V-2	N/A	
ALB-08-18-SP-(9,0)	.08 (2.0mm)	2.17 (55.0mm)	7.87 (200.0mm)	.035 (.9mm)	.098 (2.5mm)	18 (80)	V-2	N/A	
ALB-05-40-SP-(9,0)	.12 (3.0mm)	1.42 (36.0mm)	5.51 (140.0mm)	.039 (1.0mm)	.137 (3.5mm)	40 (180)	V-2	N/A	
ALB-08-40-SP-(9,0)	.12 (3.0mm)	2.17 (55.0mm)	7.87 (200.0mm)	.039 (1.0mm)	.137 (3.5mm)	40 (180)	V-2	N/A	
ALB-11-40-SP-(9,0)	.12 (3.0mm)	3.15 (80.0mm)	11.02 (280.0mm)	.039 (1.0mm)	.137 (3.5mm)	40 (180)	V-2	N/A	
ALB-07-50-SP-(9,0)	.12 (3.0mm)	1.93 (49.0mm)	7.32 (186.0mm)	.043 (1.1mm)	.177 (4.5mm)	49 (220)	V-2	N/A	
ALB-11-50-SP-(9,0)	.12 (3.0mm)	3.15 (80.0mm)	11.41 (290.0mm)	.043 (1.1mm)	.177 (4.5mm)	49 (220)	V-2	N/A	
ALB-14-50-SP-(9,0)	.12 (3.0mm)	4.06 (103.0mm)	14.17 (360.0mm)	.043 (1.1mm)	.177 (4.5mm)	49 (220)	V-2	N/A	
ALB-14-120-SP-(9,0)	.24 (6.0mm)	3.98 (101.0mm)	14.17 (360.0mm)	.059 (1.5mm)	.295 (7.5mm)	119 (530)	V-2	N/A	
						STAINLESS PAWL CABLE TIES			
						COLOR DESIGNATIONS: 9 = Natural 0 = UV Black		MATERIAL: NYLON 6/6 POLYAMIDE	
						SHEET 1 OF 1	REV.: A	DRAWING NO.: SP-A	
A	10/22/19	DW	RB	RB	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	DW	10/22/19	RB	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.102.1