


ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY	
AL-FR4A250-C	.285 (7.239mm)	.400 (10.160mm)	.138 (3.505mm)	.824 (20.929mm)	.154 (3.911mm)	.293 (7.442mm)	RED/VINYL	22-18	UL/CSA	
AL-FR4B250-C	.285 (7.239mm)	.400 (10.160mm)	.144 (3.658mm)	.824 9 (20.879mm)	.152 (3.861mm)	.293 (7.442mm)	BLUE/VINYL	16-14	UL/CSA	
AL-FR4C250-C	.285 (7.239mm)	.544 (13.828mm)	.258 (6.553mm)	.980 (24.892mm)	.157 (3.988mm)	.293 (7.442mm)	YELLOW/VINYL	12-10	UL/CSA	
							 <b>ACT</b> ADVANCED CABLE TIES INC.			
							<b>ADVANCED CABLE TIES – VINYL INSULATED FEMALE DISCONNECTS</b>			
							<b>COLOR: RED, BLUE &amp; YELLOW</b>	<b>MATERIAL:</b>  <b>VVNYL 6/6</b>		
							SHEET 1 OF 1	REV.: A	DRAWING NO.: VI-FM-DIS-A	
A	5/28/14	JA	KT	KT			DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE			JA	5/28/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.