


ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D-MIN. IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	G IN (mm) +/- .005 (.127mm)	H IN (mm) +/- .005 (.127mm)	I IN (mm) +/- .005 (.127mm)	J IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-PBA-C	.870 (22.10mm)	.410 (10.41mm)	.110 (2.79mm)	.0575 (1.48mm)	.156 (3.96mm)	.160 (4.06mm)	.032 (.81mm)	.310 (7.86mm)	.370 (9.41mm)	.250 (6.35mm)	RED/VINYL	22-18	
AL-PBB-C	.870 (22.10mm)	.410 (10.41mm)	.140 (3.56mm)	.082 (2.08mm)	.156 (3.96mm)	.160 (4.06mm)	.032 (.81mm)	.310 (7.86mm)	.370 (9.41mm)	.250 (6.35mm)	BLUE/VINYL	16-14	
													
VINYL INSULATED PIGGYBACK DISCONNECTS													
						<b>COLOR:</b> RED & BLUE			<b>MATERIAL:</b> VINYL				
B	10/21/21	DW	RB	RB	ISO DOC	SHEET 1 OF 1	REV.: B	DRAWING NO.: VI-PB-DIS-B					
A	5/28/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE				
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	6/3/14	KT	NONE				
<b>CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.</b> <b>THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.</b>													

SPC-4.10.132.2