


ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	G IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-S4A-6-C	.959 (24.359mm)	.065 (1.651mm)	.150 (3.810mm)	.450 (11.430mm)	.292 (7.417mm)	.147 (3.734mm)	.312 (7.925mm)	RED/VINYL	22-18	UL/CSA
AL-S4A-10-C	.967 (24.562mm)	.065 (1.651mm)	.150 (3.810mm)	.450 (11.430mm)	.307 (7.798mm)	.199 (5.055mm)	.312 (7.925mm)	RED/VINYL	22-18	UL/CSA
AL-S4B-6-C	.944 (23.978mm)	.091 (2.311mm)	.178 (4.521mm)	.450 (11.430mm)	.277 (7.036mm)	.147 (3.734mm)	.365 (9.271mm)	BLUE/VINYL	16-14	UL/CSA
AL-S4B-10-C	.953 (24.206mm)	.091 (2.311mm)	.178 (4.521mm)	.450 (11.430mm)	.252 (6.401mm)	.199 (5.055mm)	.393 (9.982mm)	BLUE/VINYL	16-14	UL/CSA
AL-S4C-6-C	1.080 (27.432mm)	.130 (3.302mm)	.264 (6.706mm)	.550 (13.970mm)	.285 (7.239mm)	.147 (3.734mm)	.378 (9.601mm)	YELLOW/VINYL	12-10	UL/CSA
AL-S4C-10-C	1.080 (27.432mm)	.130 (3.302mm)	.264 (6.706mm)	.550 (13.970mm)	.295 (7.493mm)	.199 (5.055mm)	.378 (9.601mm)	YELLOW/VINYL	12-10	UL/CSA
								<b>ADVANCED CABLE TIES –VINYL INSULATED SPADE TERMINALS</b>		
<b>COLOR: RED, BLUE &amp; YELLOW</b>								<b>MATERIAL:</b>  <b>VINYL</b>		
					SHEET 1 OF 1	REV.: A		DRAWING NO.: VI-SP-TERM-A		
A	5/27/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	5/27/14	KT	NONE
<b>CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.</b>										
<b>THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.</b>										