


# STAINLESS PAWL CABLE TIES



## STAINLESS PAWL CABLE TIES

DESIGNED TO PROVIDE SECURE LOCKING POINTS FOR PRECISION ADJUSTMENT

- Stainless Steel metal tooth locking mechanism
- Precision adjustment design
- Lengths from 4" to 14"
- Tensile strengths from 18 to 120 lbs.

ACT Part Number	Color	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tensile Strength	Bundle Dia. Inch/mm	UL	Per Bag	Per Case
ALB-04-18-SP-0-C	UV Black	3.93/100.0	.098/2.5	.035/0.9	18 lb.	0.94/24.0	Type 21	100	1,000
ALB-04-18-SP-9-C	Natural								
ALB-08-18-SP-0-C	UV Black	7.87/200.0	.098/2.5	.035/0.9	18 lb.	2.17/55.0	Type 21	100	1,000
ALB-08-18-SP-9-C	Natural								
ALB-05-40-SP-0-C	UV Black	5.51/140.0	.137/3.5	.039/1.0	40 lb.	1.42/36.0	Type 21	100	1,000
ALB-05-40-SP-9-C	Natural								
ALB-08-40-SP-0-C	UV Black	7.87/200.0	.137/3.5	.039/1.0	40 lb.	2.17/55.0	Type 21	100	1,000
ALB-08-40-SP-9-C	Natural								
ALB-11-40-SP-0-C	UV Black	11.02/280.0	.137/3.5	.039/1.0	40 lb.	3.15/80.0	Type 21	100	1,000
ALB-11-40-SP-9-C	Natural								
ALB-07-50-SP-0-C	UV Black	7.32/186.0	.177/4.5	.043/1.1	50 lb.	1.93/49.0	Type 21S	100	1,000
ALB-07-50-SP-9-C	Natural								
ALB-11-50-SP-0-C	UV Black	11.41/290.0	.177/4.5	.043/1.1	50 lb.	3.15/80.0	Type 21S	100	1,000
ALB-11-50-SP-9-C	Natural								
ALB-14-50-SP-0-C	UV Black	14.17/360.0	.177/4.5	.043/1.1	50 lb.	4.06/103.0	Type 21S	100	1,000
ALB-14-50-SP-9-C	Natural								
ALB-14-120-SP-0-L	UV Black	14.17/360.0	.295/7.5	.059/1.5	120 lb.	3.98/101.0	Type 21S	50	500
ALB-14-120-SP-9-L	Natural								

COO: IT

Sold in case quantities

### Related product lines



Cable Tie Removal Tool



Standard Cable Ties



Spiral Cable Wrap

**ACT**  
 ADVANCED CABLE TIES, INC.  
 245 Suffolk Lane, Gardner, MA 01440  
 Phone: 800.861.7228 - Fax: 978.630.3999  
 sales@actfs.com

